

# **REACH RX**

Multi-band network RTK rover



- Tracks GPS/QZSS1C/A, L2C, GLONASS L1OF, L2OF, BeiDou B1I, B2I, Galileo E1-B/C, E5b
- Gets a fix in 5 seconds
- · Centimetre precision
- Easy to set up: just add NTRIP
- · Comes with the ReachView 3 app
- · Pocket-sized and lightweight
- 16 hours on 1 charge
- · IP68



# **REACH RX**

## Technical specifications

#### **POSITIONING**

RTK	H: 7 mm+1 ppm
	V: 14 mm+1 ppm
:	~5 s typica <b>ll</b> y
	GPS/QZSS L1C/A, L2C,
	GLONASS L10F, L20F,
	BeiDou B1I, B2I,
	Galileo E1-B/C, E5b
els	184
	5 Hz

### CONNECTIVITY

Communication interface	Bluetooth 4.2
Ports	USB Type-C
Input data format	RTCM3
Input data protocol	NTRIP
Position output	NMEA

## **MECHANICAL**

Dimensions	172×51×51 mm
	(6.77x2.00x2.00in)
Mount	5/8"-11 UNC
Weight	250g (8.81 oz)
Ingress protection	IP68 (maximum depth of 1.5 meters up to 30 minutes)
Operating t°	-20 to + 65°C

#### **ELECTRICAL**

Autonomy	Up to 16 hrs
Battery	Li-lon 5200 mAh, 3.6 V, 18.72 Wh
Charging	USB Type-C, 5 V, 2 A
Certification	FCC, CE, IC

#### More information about Reach RX



#### **Emlid Software and services**

#### **Emlid Studio**

Easy-to-use free software to simplify your post-processing workflow.



#### ReachView 3

Android & iOS survey app for data management.



#### **Emlid NTRIP Caster**

Pass corrections between your RTK GNSS receivers over the Internet.



# CE FC

#### **GREATER CHINA DEALER**

Free shipping in Hong Kong!

